








MENNEKES CEE plugs and connectors PowerTOP plus for use under harsh conditions

with highly heat-resistant contact carrier and nickel-plated contacts

to DIN VDE 0623, EN 60309-2, colour: grey and/or colour code. Enclosure and insert made of **AMAPLAST**. Other voltages and frequencies available on request.

  			Ampere	Poles	110V	230V	400V	500V						
					50 a. 60Hz	50 a. 60Hz	50 a. 60Hz	50 a. 60Hz						
			3p 4h	4p 4h	5p 4h	3p 6h	4p 9h	5p 9h	3p 9h	4p 6h	5p 6h	3p 7h	4p 7h	5p 7h
 <p>Plug PowerTOP plus</p> <p>⚠ IP 44 Product group 2219, type 3258 shown</p>	63	3	3210	3212	3252	3255								
	63	4		3249	3252									
	63	5			3258									
 <p>Plug PowerTOP plus</p> <p>⚡ IP 67 Product group 2220, type 3325 shown</p>	63	3	3301	3303	3308	3323								
	63	4	3304	3305	3325									
	63	5			3325									
	125	3		3385*										
	125	4			3374*	3377*								
125	5			3381*										
 <p>Connector PowerTOP plus with SoftCONTACT</p> <p>⚠ IP 44 Product group 3219, type 3285 shown</p>	63	3	3270	3272	3275	3277								
	63	4		3273	3285									
	63	5			3285									
 <p>Connector PowerTOP plus 63A: with SoftCONTACT 125A: with TorsionSpringCONTACT</p> <p>⚠ IP 67 Product group 3220, type 3425 shown</p>	63	3	3401	3403	3408	3423								
	63	4	3404	3405	3425									
	63	5			3425									
	125	3		3457*										
	125	4			3469*	3472*								
125	5			3480*										

*Until the PowerTOP plus are available for 125A, the reliable PowerTOP plugs and connectors are delivered with external strain relief.